



PCB LAYOUT TOP VIEW
DIMENSIONS TOLERANCE:±0.05

- NOTES:
 1.MATERIAL:
 HOUSING:HIGH TEMP. THERMOPLASTIC, WHITE, UL 94V-0
 Plastic temperature resistance 235 degrees.
 CONTACT:PHOSPHOR BRONZE,φ=0.46mm
 2.FINISH:
 CONTACT:30u"MIN. NICKEL UNDERPLATING ALL AREA,
 GOLD PLATING UNDERPLATING ALL AREA,
 3.OPERATING TEMPERATURE:-40°C~+85°C.
 4.JACK CAVITY CONFORMS TO FCC RULES AND
 REGULATIONS PART 68, SUBPART F
 5.THE SIZE OF THE PRODUCT MOUTH IS SUBJECT TO FCC REGULATIONS
 6.吊重要求达到5KG。(吊重方式: 拉力往水平0°, 45°, -45°, 左45°, 右45° 各拉1分钟;)

PART NUMBER:
 JD1A-0 0 H 1-0 0 A M
 Housing PBT WHITE
 香菇柱
 Gold Plated G/F u"
 Contact PIN 3.20mm
 LED Code W/O LED

REV.	ECN. NO.	DRAWN	DATE	EC.content
A.0	NEW	Tony	20/11/2019	
A.1	EN2101003	ALLEN	01/07/2021	增加吊重管控
A.2	EN2101007	LiQiqing	01/20/2021	更改吊重5KG管控



QUALITY CONTROL ITEM	GENERAL TOLERANCE	PART NO.:
APPROVED	.X± 0.38 X:± 2'	JD1A-00H1-00AM
CHECKED	.XX± 0.25 X:± 1'	TITLE:RJ45 CONN. JD1A.1X1 CONNCTOR
DRAWN	.XXX± 0.13	W/OLED, 10P8C,0.1u" Min
	UNIT: mm	SCALE: 1:1
		SHEET: 1/1
		REV.: A.2